



KEY FEATURES

Time-saving features for efficient GIS data collection and maintenance

Seamless GPS control in the field for quality position data

Complete support for vector or raster map backgrounds for enhanced verification of field data

Runs on Trimble's complete portfolio of ruggedized Windows Mobile field computers

H-Star data collection for high accuracy with compatible Trimble receivers and handhelds

Real-time and postprocessed GLONASS support with the GPS Pathfinder ProXRT receiver

Data collection for Trimble DeltaPhase processing provides improved postprocessed accuracy

FIELD SOFTWARE FOR QUALITY GIS DATA

The TerraSync™ software is powerful field software, designed for fast and efficient data collection and maintenance. Teamed up with a supported Trimble® GPS receiver and a field computer of your choice, it's all you need to collect quality feature and position data for your geographic information system (GIS).

Effortless data collection

Whether you need to collect many identical assets or a range of assets with many different attributes, the TerraSync software lets you capture high quality data quickly and easily. You can create a data dictionary based on the enterprise GIS so that features, attributes, and acceptable attribute values match the GIS data structure. Now you can be sure that the data you collect will always meet the decision makers' requirements.

Using a data dictionary improves efficiency and ease of use in the field, with time-savers like pre-defined pick lists and automatic generation of date and time values. And, to make your field session effortless, the TerraSync software puts smart features—like map-centric operation, graphical status display, and the ability to record a position offset if you can't get right to the feature— at your fingertips.

The TerraSync software makes it easy for you to incorporate photo capture into your data collection workflow when using a Trimble handheld with an integrated camera. TerraSync enables you to take and preview photos, automatically attaches them to the current feature, and stamps each photo with the time, date and location at which it was taken.

Smart data maintenance

When you need to go back into the field to verify and update your GIS data, the TerraSync software makes the job as quick as possible. Waypoint files can be created within TerraSync software, or imported from GPS Pathfinder® Office software, to help you navigate in the field. You can sort and filter imported features from your GIS, based on the order you want to visit them. Features can be viewed as a simple list, or on the color-coded map with an aerial photo or satellite image in the background for reference. To revisit an asset, select the corresponding feature from the list or map, and then let the intuitive

graphical GPS navigation tools guide you to precisely where you need to go. TerraSync even integrates with popular turn-by-turn navigation software such as CoPilot Live 7 Professional. When you start navigating to a feature or waypoint, the TerraSync software passes that location to your turn-by-turn software, which quickly and safely guides you to your destination. Once you have reached a waypoint, the TerraSync software marks it as visited. If you edit an existing feature, the TerraSync software marks it as updated.

Quality control made easy

With the TerraSync software it's a breeze to collect data to your required accuracy, either when collected in real time in the field, or to that predicted after postprocessing. Simply use the accuracy-based logging settings to specify the GPS data quality that your enterprise GIS demands and let TerraSync do the rest. To make sure your time in the field will be productive, use the Plan section to view a graphical prediction of the GPS satellite constellation and identify the best times for data collection.

The TerraSync software integrates seamlessly with a range of Trimble GPS receivers to give you the high quality data you need. You can differentially correct your data back in the office, use real-time differential GPS, or both—the choice is yours. For extra precision, collect H-Star™ data with a GPS Pathfinder ProXRT receiver, a GPS Pathfinder ProXH™ receiver, or a GeoXH™ handheld. Completely integrated with existing data collection workflows, H-Star technology makes high accuracy data collection faster and easier than ever before. Alternatively, with a GeoXT™ or Juno™ series handheld, or a ProXT™ receiver, you can achieve optimal GPS code processing accuracy with the new Trimble DeltaPhase™ technology.

Whichever combination of GPS receiver and correction method suits your needs, you can rely on clear feedback on expected accuracy while you work, providing confidence in collecting high quality data for your GIS.

Simple, effective, and productive in the field—the TerraSync software is the easy-to-use tool you need to collect and maintain quality GIS data.



FEATURES AND OPTIONS

Key features

- Collect position, feature, and attribute data
- Industry-leading GNSS receiver configuration and control
- Fast, real-time map display supports multiple raster and vector background maps
- Graphical screens for navigation back to selected features
- Integrates with CoPilot Live 7 Professional software for TerraSync, and TomTom Navigator 6 software
- Waypoint support for productive use of field time
- Data dictionary editor for customized data collection requirements
- Data dictionary capabilities allow in-field modifications to data dictionaries
- Mission planning to find the best time to collect data
- Supports multimedia attributes such as voice and image files
- Optimized for Trimble handhelds with integrated digital cameras
- Send and receive files by e-mail directly in the field
- Supports ESRI Shapefiles

GPS accuracy

- Real-time differential correction (available sources depend on GNSS receiver and base station used)
- Improved position accuracy with differential postprocessing of GPS and GLONASS data
- Achieve up to decimeter (10 cm / 4 inch) accuracy using real-time or postprocessed H-Star technology (dependent on H-Star-capable receiver and antenna combination used)
- Supports logging of DeltaPhase data for optimal code accuracy after postprocessing
- Support for collection of RTK data with Trimble 5800, R8, and R8 GNSS receivers

Software editions

- TerraSync Standard edition for data collection
- TerraSync Professional edition for data collection and maintenance

For a product comparison of the Standard and Professional editions visit: www.trimble.com/mgis_prodcomp.shtml

Supported GPS receivers

- GPS Pathfinder ProXT receiver
- GPS Pathfinder ProXH receiver
- GPS Pathfinder ProXRT receiver
- GPS Pathfinder XC receiver
- Trimble 5800 receiver
- Trimble R8 receiver
- Trimble R8 GNSS receiver

Supported field computers with integrated GPS

- GeoXH handheld
- GeoXT handheld
- GeoXM™ handheld
- Juno SB handheld
- Juno SC handheld
- Trimble Nomad® G series handheld
- Trimble Recon® GPS XC edition
- Trimble Yuma® rugged tablet computer

Supported field computers

- Trimble Ranger™ handheld
- Trimble Recon handheld

Available languages

- Chinese (Simplified)
- English
- French
- Russian
- German
- Italian
- Japanese
- Korean
- Portuguese
- Spanish

RECOMMENDED PLATFORM

Windows Mobile field computer

Operating system Windows Mobile® version 5.0 software or Windows Mobile version 6

Processor type ARM or XScale

Processor speed 200 MHz or faster

Memory 32 MB RAM at least 8 MB free memory

Input/output Serial cable and RS-232 serial port (or appropriate adaptor) or Bluetooth® technology for connection to GPS Pathfinder Pro series receiver or GPS Pathfinder XB receiver

Display Color touch screen (240 × 320 pixels or larger) Reflective screen (or other screen suitable for outdoor viewing)

Windows field computer

Operating system Windows® XP (Home, Professional, or Tablet PC Edition) (32- or 64-bit versions) or Windows Vista® or Windows 7 (Home, Business, or Ultimate editions) (32- or 64-bit versions)

Processor speed 500 MHz or faster

Memory 64 MB RAM at least 8 MB free memory

Input/output Serial cable and RS-232 serial port (or appropriate adaptor) or Bluetooth technology for connection to GPS Pathfinder Pro series receiver

SUPPORTED BACKGROUND FILE FORMATS

Vector formats

- Trimble SSF format (.ssf, .cor, .imp)
- ESRI Shapefiles (.shp)

Raster (image) formats

- JPEG (.jpg)
- JPEG 2000 (.jp2, .j2c)
- Enhanced Compression Wavelet (.ecw)
- MrSID (.sid)
- TIFF (.tif)
- Windows bitmap (.bmp)

GPS POSTPROCESSING OPTIONS

- GPS Pathfinder Office software
- Trimble GPS Analyst™ extension for ESRI ArcGIS Desktop software

Specifications subject to change without notice.

© 2000–2010, Trimble Navigation Limited. All rights reserved. Trimble, the Globe & Triangle logo, GeoExplorer, GPS Pathfinder, Nomad, Recon, and Yuma are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. DeltaPhase, GPS Analyst, GeoXH, GeoXM, GeoXT, H-Star, Juno, ProXH, ProXT, and Ranger are trademarks of Trimble Navigation Limited. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Trimble Navigation Limited is under license. Windows, Windows Mobile, and Windows Vista are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. All other trademarks are the property of their respective owners. PN 132785 (02/10)



YOUR LOCAL TRIMBLE OFFICE OR REPRESENTATIVE

NORTH & SOUTH AMERICA

Trimble Navigation Limited
10355 Westmoor Drive
Suite #100
Westminster, CO 80021
USA
+1-720-587-4574 Phone
+1-720-587-4878 Fax

EUROPE & AFRICA

Trimble Germany GmbH
Am Prime Parc 11
65479 Raunheim
GERMANY
+49-6142-2100-0 Phone
+49-6142-2100-550 Fax

ASIA-PACIFIC & MIDDLE EAST

Trimble Navigation
Singapore PTE Limited
80 Marine Parade Road
#22-06 Parkway Parade
Singapore, 449269
SINGAPORE
+65-6348-2212 Phone
+65-6348-2232 Fax

